AMENDMENTS TO THE CLAIMS

Please amend the claims as follows.

- 1. (Currently Amended) A method for the mitigation of pet malodor(s) on surfaces comprising contacting said malodor(s) with an aqueous liquid deodorizing composition to entrap said malodor(s) in a minute, transparent residue or film, the composition eontaining consisting essentially of: about at least 0.01% to about 10% of a[[n]] dialkali metal tetraborate n-hydrate (with n being an integer form 0 to 10), 0.1-3% water soluble/dispersible polymer, 1-25% water soluble/dispersible volatile solvent, and at least 75% water.
- 2. (Original) The method of claim 1 wherein said composition further comprises at least one aesthetic and/or functional additive.
- 3. (Original) The method of claim 1 wherein said dialkali metal tetraborate n-hydrate is selected from the group consisting of borax pentahydrate and borax decahydrate.
- 4. (Currently Amended) The method of claim 1 wherein said polymer is selected from the group consisting of water soluble to dispersible polymers having a molecular weight of below about 2,000,000[[d]] Daltons.
- 5. (Original) The method of claim 1 wherein said solvent is selected from the C_{1-6} alkanols and C_{1-24} glycol ethers.
- 6. (Currently Amended) A product for mitigating or eliminating pet malodor(s) on surfaces to which the malodors have been applied, the product-comprising consisting essentially of: an aqueous liquid deodorizing composition, the composition containing about at least 0.01% to about 10% of a[[n]] dialkali metal tetraborate n-hydrate (with n being an integer form 0 to 10), 0.1-3% water soluble/dispersible polymer, 1-25% water soluble/dispersible volatile solvent, and at least 75% water.

- 7. (Currently Amended) A container for dosing a liquid malodor counteractant on pet malodor(s) for the mitigation or elimination thereof, said liquid malodor counteractant eomprising consisting essentially of: an aqueous liquid deodorizing composition containing about at least 0.01% to about 10% of a[[n]] dialkali metal tetraborate n-hydrate (with n being an integer form 0 to 10), 0.1-3% water soluble/dispersible polymer, 1-25% water soluble/ dispersible volatile solvent, and at least 75% water, wherein said composition is capable of forming a minute, transparent residue or film capable of entrapping malodor(s).
- 8. (Previously Presented) The method of claim1 wherein said malodor(s) are form ammonia formation due to decomposition of urea present in animal waste.
- 9. (Previously Presented) The method of claim 6 wherein said malodor(s) are from ammonia formation due to decomposition of urea present in animal waste.
- 10. **(Previously Presented)** The container of claim 7 wherein said malodor(s) are form ammonia formation due to decomposition of urea present in animal waste.
- 11. (Currently Amended) The method for the mitigation of pet malodor(s) on surfaces comprising contacting said malodor(s) with an aqueous liquid deodorizing composition wherein the malodor(s) are from ammonia formation due to decomposition of urea present in animal waste, and wherein the composition eomprises consisting essentially of: about at least 0.01% to about 10% of a[[n]] dialkali metal tetraborate n-hydrate (with n being an integer from 0 to 10), 0.1-3% water soluble/ dispersible polymer, 1-25% water soluble/ dispersible volatile solvent, and at least 75% water.
- 12. (Previously Presented) The method of claim 11 wherein said composition further comprises at least one aesthetic and/or functional additive.
- 13. (Previously Presented) The method of claim 11 wherein said dialkali metal tetraborate n-hydrate is selected from the group consisting of borax pentahydrate and borax decahydrate.

- 14. (Currently Amended) The method of claim 11 wherein said polymer is selected from the group consisting of water soluble to dispersible polymers having a molecular weight of below about 2,000,000 [[d]] Daltons.
- 15. (Previously Presented) The method of claim 11 wherein said solvent is selected from the C_{1-6} alkanols and C_{1-24} glycol ethers.